

T8 – Asia Wiring Configuration

Asia Wiring method



Kuo Lian In-house Spec T8 LED Tube (Non-Dimmable)				
Model	T8-18KL6500	T8-20L6500	T8-22KL6500	T8-24KL6500
Power	18W	20W	22W	24W
Brightness	2160Lm	2400Lm	2500Lm	22880Lm
Voltage (In)	AC170-265V 50/60Hz			
CCT	6500K(+/-500K)			
Ingress Protection	IP20			
Material	Glass			
Usage Condition	-10°C to 45°C			
	Max 8 pcs in Single loop			
	Up to 12 hours daily			
Warranty	1 Year Carry-in			

Kuo Lian In-house Spec T8 LED Tube		
Model	T8-18KL6500	T8-9L6500
Power	18W	9W
Brightness	2700Lm	900Lm
Voltage (In)	AC85-265V 50/60Hz	AC170-265V 50/60Hz
CCT	6500K(+/-500k)	6500K(+/-500K)
Ingress Protection	IP20	IP20
Material	AL+PC	Glass
Usage Condition	-10°C to 45°C	
	Max 8 pcs in Single loop	Max 8 pcs in Single loop
	Up to 18 hours daily	Up to 12 hours daily
Warranty	2 Year Carry-in	1 Year Carry-in

LED Tubes Light – Asia Wiring Configuration (Non-Dimmable)			
➤ T8-18W (1200mm) 6000K Glass	➤ T8-20W (1200mm) 6000/3000K Glass	➤ T8-22W (1200mm) 6000K Glass	T8-24W (1200mm) 6000K Glass
➤ T8-9W (600) 6000/3000K Glass		➤ T8/18W/1200/6000K AL+PU	
➤ T8-18W(1200)6000K AL+PU Sensor (Total Off)		➤ T8-9W (600)6000K AL+PU Sensor (Total Off)	
LED Tubes Light – Europe Wiring Configuration (Non-Dimmable)			
➤ Philips T8 Corepro 8/16W LED 865/840	➤ Philips T8 Corepro 8W LED 865/840	➤ OSRAM ST8E 18W 6500K 1200 mm	➤ OSRAM ST8A 13W 6500K 1200 mm