

## T8 Fitting

T8 Batten Fitting	T8 IP65 Fitting																														
 <p>140 Batten -Single tube 4ft batten 120 Batten-Single tube 2ft batten</p>  <p>240 Batten -Double tube 4ft batten 220 Batten-Double tube 2ft batten</p> <p>Width*Height- 50*40mm</p>	<p><b>DAMP PROOF HOUSING</b>   Damp-proof luminaire for T8 LED lamps</p>  <p><b>LEDVANCE</b></p> <p><b>Materials &amp; Colors</b></p> <table border="1"> <tr><td>Product color</td><td>Grey</td></tr> <tr><td>Housing color</td><td>Gray</td></tr> <tr><td>Body material</td><td>Polycarbonate (PC)</td></tr> <tr><td>Cover material</td><td>Polycarbonate (PC)</td></tr> <tr><td>Light emitting surface material</td><td>Polycarbonate (PC)</td></tr> <tr><td>Glow Wire Test according to IEC 60695-2-12</td><td>650 °C</td></tr> <tr><td>Mercury content</td><td>0.0 mg</td></tr> </table> <p><b>Application &amp; Mounting</b></p> <table border="1"> <tr><td>Ambient temperature range</td><td>-30...+40 °C</td></tr> <tr><td>Temperature range at storage</td><td>-20...+80 °C</td></tr> <tr><td>Type of connection</td><td>Screwless terminal, 3-Pole</td></tr> <tr><td>Type of protection</td><td>IP65</td></tr> <tr><td>Protection class IK (shock resistance)</td><td>IK08</td></tr> <tr><td>Mounting type</td><td>Suspended/Surface</td></tr> <tr><td>Mounting location</td><td>Ceiling / Wall</td></tr> <tr><td>Standards</td><td>CE</td></tr> </table> 	Product color	Grey	Housing color	Gray	Body material	Polycarbonate (PC)	Cover material	Polycarbonate (PC)	Light emitting surface material	Polycarbonate (PC)	Glow Wire Test according to IEC 60695-2-12	650 °C	Mercury content	0.0 mg	Ambient temperature range	-30...+40 °C	Temperature range at storage	-20...+80 °C	Type of connection	Screwless terminal, 3-Pole	Type of protection	IP65	Protection class IK (shock resistance)	IK08	Mounting type	Suspended/Surface	Mounting location	Ceiling / Wall	Standards	CE
Product color	Grey																														
Housing color	Gray																														
Body material	Polycarbonate (PC)																														
Cover material	Polycarbonate (PC)																														
Light emitting surface material	Polycarbonate (PC)																														
Glow Wire Test according to IEC 60695-2-12	650 °C																														
Mercury content	0.0 mg																														
Ambient temperature range	-30...+40 °C																														
Temperature range at storage	-20...+80 °C																														
Type of connection	Screwless terminal, 3-Pole																														
Type of protection	IP65																														
Protection class IK (shock resistance)	IK08																														
Mounting type	Suspended/Surface																														
Mounting location	Ceiling / Wall																														
Standards	CE																														

**T8 Tube LED Fixtures**



Bracket



Mirror Louvre  
240/340/440/220/ 320/420



Racer Paragon



Racer Batten  
140/240



IP65 Weather Proof

**SAVING ENERGY**